

# 316 FLOOR FINISH REMOVER

The No. 316 Floor Finish Remover can be used on all floors except linoleum, unsealed wood and cork. This fast acting, low odor product quickly penetrates and completely liquefies multiple layers of floor finish, wax and water-based seals. Its low odor qualities makes it a preferable product for health care, hospitals, nursing homes and school facilities.

- Ultra low odor - pleasant to use
- Rapid emulsification - reduces labor
- Works in cold water - economical
- Low foaming - user friendly

- Non-flammable
- Safe in septic systems
- Readily biodegradable
- Low aquatic toxicity
- No ozone depleting substances
- Phosphate free
- No harmful chemical runoff
- Low V.O.C. content
- Non toxic

**APPEARANCE:** Clear and colorless  
**pH** (as concentrate): typically 10.0 - 11.5  
**Specific Gravity:** typically 1.00  
**Foam Level:** Low

**DOES NOT CONTAIN:**

- Abrasives • Caustic alkalis • Agressive biocides • Harmful chemicals • Chlorinated solvents

**APPLICATION METHODS:**

This product is formulated to work effectively with cold water. Cold water is recommended to help save energy used to heat water.

1. Mix according to dilution chart and depending upon the build-up conditions.
2. Apply solution liberally to the floor.
3. Keep floor wet for 5 - 10 minutes to allow stripper time to work.
4. Machine scrub with a stripper pad and floor machine or autoscrubber.
5. Pick up with wet vac or autoscrubber.
6. Pick up stripping residues with clean water and a damp mop.
7. Let floor dry thoroughly.
8. Apply a new foundation of Sprayway No. 315 Metal-Free Floor Finish.

See label for other directions for use.



This product has been formulated in a partnership with the Design for the Environment Program.



This product meets the Green Seal™ environmental standard for industrial and institutional cleaners based on its reduced human and environmental toxicity and reduced volatile organic compound content.



Certified Floor Care Products CCD-147